

JHM USA 5

Eco magnetic core drill up to 2-3/8 in [60 mm]

Order number:: 7 272 54 61 12 4



With 2-speed gearbox for drilling in the workshop to depths up to 75 mm.

- Uniform-torque motor for demanding core drilling.
- High concentricity and reliable core ejection due to special bore spindle guides.
- Solid, massive construction in die-cast aluminum for work under difficult conditions.
- Integrated cooling tank.
- Internal motor cable routing.
- Accessory handle for easy carrying of tool.
- Hand feed wheel can be mounted on either side.
- Mechanical 2-speed gearbox.
- Extra-long drill shaft for drilling depths up to 3 in (75 mm).



JHM USA 5

Eco magnetic core drill up to 2-3/8 in [60 mm]

Order number:: 7 272 54 61 12 4

Technical data

HSS annular cutters max. dia.	2 3/8 In
Mag base, max. drilling depth	3 In
Power consumption	1,400 Watts
Power output	770 Watts
No-load speed: 1st gear	330 rpm
No-load speed: 2nd gear	660 rpm
Load speed: 1st gear	180 rpm
Load speed: 2nd gear	340 rpm
Annular cutter holder	3/4 in Weldon
Stroke	3 5/8 In
Magnetic holding force	2,420 lbs
Magnetic base dimensions	7 1/2 x 4 In
Cable with plug	12 1/2 ft
Weight according to EPTA	52.7 lbs
Corded	X

Price includes:

1 case
1 coolant tank
1 safety strap
1 chip hook
4 pilot pins
1 allen key 5 mm
1 touch guard
1 carrying handle